

AS-CAM-18HDMI4K-A			
Total Pixels	3,952(H) x 2,320(V) = 9.17M pixels	Eff. Pixels	3864(H) x 2180(V) = 8.42M pixels
Video Modes	3840x2160 - 30/25fps 2560x1440p - 30/25fps 1920x1080 - 30/25 fps 1280x720 - 30/25 fps CVBS	Viewing Angle (D x H x V)	Wide: 65.3° x 58.5° x 35° Tele: 4.2° x 3.7° x 2.1°
Aperture	F1.61 (wide) ~ F4.13 (tele)	F. length	f = 6.8 mm ~ 120 mm
Shutter spd.	1/1 ~ 1/60,000 sec	Min. Distance	50cm
Zoom speed	0 (slow) -7 (fast)	AGC	0-10 steps
Min. Illum.	1/30s, 72dB 0.012lux color 1/30s, 72dB 0.0019lux B/W	Exposure	Auto / Iris Priority / Shutter Priority / Manual
S/N ratio	>50dB (AGC off)	DWDR	Off / Auto / Manual
DNR	2D / 3D, 0-15 steps each	Day & Night	Day / Night
White Bal.	Auto / Indoor / Outdoor / One Push / Manual	DSS	Off / 2x / 4x / 8x / 16x / 32x (/64x : 60 or 50fps mode only)
Protocol	Pelco-P / Pelco-D / VISCA	Flickerless	Off / On / Auto
Baud Rate	2400 / 4800 / 9600 / 19200 / 38400 / 57600 / 115200 bps	Other features	Motion detection, Defog, Area intrusion, line crossing, Privacy, BLC / HLC.
Voltage	9-15V DC	Current	500mA @12V
Storage	-20°C – +60°C (Humidity: 0%RH – 90%RH)	Operation	-10°C – +50°C (Humidity: 0%RH – 90%RH)
Dimensions	50(W) x 62(H) x 98(D) (mm)	Weight	293g



ORDERING INFORMATION

PART NUMBER	DESCRIPTION
AS-CAM-18HDMI4K-A	Harrier 18x AF-Zoom HDMI 4K Camera
AS-CAM-18HDMI4K-EVAL-A	Evaluation Kit for the Harrier 18x AF-Zoom HDMI 4K Camera

CONTACT DETAILS

Europe & APAC:

Active Silicon Ltd
Pinewood Mews, Bond Close, Iver,
Bucks, SL0 0NA, UK.

Tel: +44 (0)1753 650600
Fax: +44 (0)1753 651661
Email: info@activesilicon.com
Website: www.activesilicon.com

Americas:

Active Silicon, Inc.
479 Jumpers Hole Road, Suite 301,
Severna Park, MD 21146, USA.

Tel: +1 410-696-7642
Fax: +1 410-696-7643
Email: info@activesilicon.com
Website: www.activesilicon.com