

Reka Glue Gun Pneumatic
REKA 气动热熔胶枪系列

reka

TR 70 LCD Cartridge Gun
TR70 LCD 铝桶装 PUR 专用热熔胶枪



Fig. TR 70 LCD Cartridge Gun

Made in Germany

Subject to technical modifications

The TR 70 LCD cartridge gun applies hot melt adhesives from 310 ml aluminium cartridges in dots, beads, or other standard nozzle forms.

TR70LCD 铝桶装 PUR 专用热熔胶枪专为使用 310 毫升铝桶装 PUR 热熔胶而设计制造。用于点状或者条状涂胶

The TR 70 LCD has considerable advantages: It works with 310 ml aluminium cartridges. The appropriate nozzle is screwed with the adapter on to the aluminium cartridge, thus enabling quick cartridge change.

TR70LCD 使用喷嘴连接器可以很方便的将喷嘴连接到铝桶上,同样也可以很方便快捷的更换用完的铝桶

The TR 70 LCD is capable of working with PUR hot melts. PUR HMs distinguish themselves by an extremely high thermal stability.

TR80LCD 专门用于 PUR 热熔胶的点状/条状涂胶应用.PUR 热熔胶具有优异的热稳定性

The electronic temperature control is integrated into the handle for easy operation.

胶枪内整合有温度控制器,可以很方便的进行操作。

It provides an optimum working temperature simultaneously ensuring a careful handling of the material to be glued. The electronic system is easily adjustable.

温度控制器保证最佳的胶水工作温度.可以非常方便地进行温度调节

Due to the light weight (1400 g) and balanced design working with the appliance is not tiring and your wrist will not be strained.

非常轻便,方便客户使用

Thanks to the variety of accessories available you can design an appliance adapted to your individual requirements.

对于客户的不同需求,有多种附件可供选择.

An optional stationary stand with foot switch is helpful when glueing small parts leaving both hands free. Various nozzles, foot switches, balancers, gun stands and stands for stationary operation complete the program.

在很小的工件上涂胶时,可以选用安装支架和脚踏开关,以方便操作. 有多种附件 比如各种喷嘴\脚踏开关\平衡器\安装支架等可供选择

Technical Data 技术参数

TR 70 LCD	
<i>Voltage</i> 电压	230 V (120 V on request 可提供 120v 类型)
<i>Heating capacity</i> 加热功率	400 W
<i>Air pressure for glue max.</i> 最大出胶气压	approx. 90 psi/6 bars *
<i>Air consumption max.</i> 最大用气量	100 l / min.
<i>Temperature control</i> 温度控制	Electronic 电子式
<i>Temperature control range</i> 温度控制范围	50 – 185°C
<i>Overheat protection</i> 超温保护	thermal protector
<i>Fuse</i> 总保险	4 A
<i>Heat-up time</i> 预热时间	3 – 10 min. **胶水种类不同时间略有差异
<i>Length of electric cord</i> 电源线长度	approx. 8,5 m
<i>Contents of aluminium cartridge</i> 适用铝桶	310 ml
<i>Max. application of glue</i> 最大出胶量	310 ml per minute 每分钟 310 毫升
<i>Weight handgun</i> 重量	1400 g

Accessories 可选附件**Pneumatic foot switch** 气动脚踏开关**Stand with pressure regulator and manometer** 带调压表和调压阀的调压台**Stationary equipment** 安装支架**Balancer** 平衡器**Various additional nozzles** 多种喷嘴**中国地区总代理:**

北京高端科技发展有限公司

Tel: 010-57037756 / 13910680170

Fax 010-67713200

Internet: www.hetek.com.cnEmail: yangfeng@hetek.com.cn**Reka Klebetechnik GmbH & Co.KG**

Siemensstr. 6

D-76344 Eggenstein

Tel. +49 721 / 970 780

Fax +49 721 / 705 069

Internet: www.reka-klebetechnik.deEmail: info@reka-klebetechnik.de